

NASTRUCK RULES

Will run on the oval

**If It's Not Mentioned
It's Not Legal**

- Chassis:** Any 4" stamped steel chassis, you may NOT interchange parts, cut, grind or bend chassis from original shape.
- Bodies:** JK Nastruck style body only. Bodies must be fully painted with clear windows and visible front wheels. Cut on the cut line and mounted even and level with the bottom of the frame. Look like a nastruck with sponsors and Three numbers one on the top and one on each side
- Tires:** Front: Any 1/2 or 5/8" diameter wheels metal with o ring, in original location
Rear: Any black foam or rubber
- Axles:** front axle 1/16", rear axle 1/8 or 3/32" steel only
- Gears:** any 48 or 64 pitch gears only
- Motor:** Parma 16D Motor #501 sealed motor only. may change springs and brushes and solder the motor bushing in.

Track clearance tech will be .047" at the rear of the car from tire to tire
cars may not exceed 3 1/4" width
motors, lead wire, front axles, rear axle bushings,
rear chassis brace, may be soldered in.
rear axle bushing holes may be enlarged to level rear axle
must use body clips
independent front wheels are permitted
may change lead wire
may use any guide flag & nut
remember

**If It's Not Mentioned
It's Not Legal**

**Be the best racer you can be
support the sport by being the best
corner marshal you can be
without marshals we have no races
everyone needs to help
thanks**